



UTILITY ENTERPRISES, INC.
700 MAIN STREET, WESTBURY, NY 11590
(516) 997-6300 - FAX # (516) 997-6345

MATERIAL SAFETY DATA SHEET

ODOR KILL POWDER FUEL OIL DEODORIZER

FOR CHEMICAL EMERGENCY: Spill, Leak, Fire, Exposure, or Accident - Call INFOTRAC - Day or Night: **1-800-535-5053**
THIS MSDS COMPLIES WITH 29 CFR 1910.1200 (HAZARD COMMUNICATION STANDARD) **IMPORTANT:** Read this MSDS before handling & disposing of this product. Pass this information on to employees, customers and users of this product.

PRODUCT IDENTIFICATION

DOT Shipping name:	MAGNESIUM ALUMINUM SILICATE	CAS NO.: MIXTURE
Chemical Family:	ATTAPULGITE	UN/NA #: N/A
DOT Hazard Class:	NONE	DATE OF ISSUE: 4/11

SECTION I - HAZARDOUS INGREDIENTS/EXPOSURE LIMITS

Hazardous Ingredients:	CAS #	TLV/PEL	AGENCY	TYPE	SARA-313(% Range)
NONE					

SECTION II - EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: Move person away from exposure and into fresh air. If irritation or redness develops, flush eyes with clean water and seek medical attention. **Seek medical attention.**

SKIN CONTACT: Remove contaminated shoes and clothing and cleanse affected areas thoroughly by washing with mild soap and water. If irritation persists **seek medical attention.**

INHALATION: (breathing) Not expected to be a hazard under normal operating conditions.

INGESTION: (swallowing) Rinse mouth with water. **Seek medical advice.**

SECTION III - HEALTH HAZARDS / ROUTES OF ENTRY

EYE CONTACT: One or more components of this material may be an eye irritant.

SKIN CONTACT: Continuous contact with this material may cause drying of skin. Chemical itself is an irritant or sensitizer.

SKIN ABSORPTION: No symptoms of toxicity are anticipated by this route .

INHALATION: (breathing) Not expected to be a hazard under normal operating conditions.

INGESTION: (swallowing) Ingestion of large quantities may cause irritation of digestive tract, intestinal obstruction or constipation.

SECTION IV - SPECIAL PROTECTION INFORMATION

VENTILATION: Adequate ventilation is recommended.

RESPIRATORY PROTECTION: Not necessary under normal use.

PROTECTIVE GLOVES: The use of gloves impermeable to the specific material handled is advised to prevent possible irritation.

EYE PROTECTION: Approved eye protection to safeguard against potential eye contact, irritation or injury is recommended.

SECTION V - REACTIVITY DATA

STABILITY: Stable

INCOMPATIBILITY: (materials to avoid) This product is incompatible with: *Oxidizing agents, strong acids and bases*

HAZARDOUS DECOMPOSITION PRODUCTS: Thermal decomposition in the presence of air may yield carbon monoxide, carbon dioxide.

HAZARDOUS POLYMERIZATION: Will not occur

SECTION VI - SPILL OR LEAK PROCEDURES

PRECAUTIONS IN CASE OF LEAK OR SPILL: If a spill occurs, material should be cleaned up with an appropriate absorbent.

WASTE DISPOSAL METHOD: Dispose of product in accordance with local, county, state and federal regulations.

SECTION VII - STORAGE AND SPECIAL PRECAUTIONS

HANDLING AND STORAGE PRECAUTIONS: Do not get in eyes, skin or clothing. Keep containers tightly closed and dry. Use and store this product with adequate ventilation. Use good personal hygiene practices. Dispose of containers in an environmentally safe manner and in accordance with governmental regulations.



UTILITY ENTERPRISES, INC.
 700 MAIN STREET, WESTBURY, NY 11590
 (516) 997-6300 - FAX # (516) 997-6345

MATERIAL SAFETY DATA SHEET

ODOR KILL POWDER FUEL OIL DEODORIZER

SECTION VIII - FIRE AND EXPLOSION HAZARD DATA

EXTINGUISHING MEDIA: Extinguish with dry chemical, CO₂, or a universal type foam.
FIRE AND EXPLOSION HAZARD: May decompose during contact with flames, heating elements, or in combustion engines releasing irritating gases.
FIRE FIGHTING PROCEDURES: Wear appropriate protective equipment including respiratory protection as conditions warrant (see Section IV). Stop spill/release if it can be done without risk. Water spray may be useful in minimizing or dispersing vapors and cooling equipment exposed to heat and flame.

SECTION IX - PHYSICAL DATA

APPROXIMATE BOILING POINT (DEG F):	N/A	PER CENT VOLATILE:	N/A
SPECIFIC GRAVITY (68 F):	2.4	FLASH POINT (TCC, DEG F):	NON-FLAMMABLE
RELATIVE EVAPORATION RATE (ESTIMATED):	N/A	PER CENT SOLUBILITY IN WATER:	0
VAPOR PRESSURE @20C mmHg (CALCULATED):	N/A		

SECTION X - OTHER REGULATORY DATA

<p><u>SARA</u></p> <p><i>SECTION</i> 302: NOT LISTED <i>SECTION</i> 311 & 312: NOT LISTED <i>SECTION</i> 313: See Section I.I</p> <p><u>TSCA</u></p> <p>All components are in full compliance with the TSCA inventory.</p> <p><u>RCRA</u></p> <p>Waste material would be a D001</p>	<p><u>HMS</u></p> <p>Health: 0 Flammability: 0 Reactivity: 0</p> <p><u>CALIFORNIA PROPOSITION 65</u></p> <p>NOT LISTED</p> <p><u>CERCLA</u></p> <p>NOT LISTED</p>
--	--

CARCINOGENICITY:
 NOT LISTED with NTP or IARC.

NOTICE

The supplier disclaims all expressed or implied warranties of merchantability or fitness for a specific use, with respect to the product or the information provided herein, except for conformation to contracted specifications. All information appearing herein is based upon data obtained from manufactures and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency. Conditions of use are beyond our control, and therefore users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume risks of their use, handling, and disposal of the product. Users also assume all risks in regards to the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein, and does not relate to its use in combination with any other material or process.